



PPS Series Pendant Stations

Single-Speed, Two-Speed, Three-Speed and Accessories

- Up to Five Motions plus Accessories
- Pre-Wired Stations Available from Factory
- Compact Design
- Double-Break Silver-Plated Switch Contacts
- LED Pilot Light for Cool Trouble-Free Operation
- Polyphenylene Oxide Construction
- Easy-to-Read Button Name Plates
- NEMA 1, 3, 4, 4x and 12
- UL Listed and CSA Approved
- Wide Temperature Range: -10°F to +150°F
- Rubber Bushing and Water-Resistant Packing
- IP 65 Rated

Each enclosure includes a legend plate sheet, Neoprene cord grip, strain relief attachment and Neoprene boots.

Catalog Number	Enclosure Type	Dimension — Inches			Weight Lbs.	Cable Diameter Opening— Inches †	
		Width	Depth	Length		R	L
PC Style Enclosures							
PC-1	Two-Button	3-1/8	1-7/8	5-1/4	1/2	.412 - .540	—
PC-2	Four-Button	3-1/8	1-7/8	7-3/4	3/4	.532 - .660	—
PC-3	Six-Button	3-1/8	1-7/8	11-1/4	1	.532 - .660	.652 - .780
PC-4	Eight-Button	3-1/8	1-7/8	13-1/8	1-1/2	.652 - .780	.760 - .886
PC-5	Ten-Button	3-1/8	1-7/8	16	1-3/4	—	.760 - .886
PT Style Enclosures							
PT-3	Six-Button	3-1/8	2-3/4	11-1/4	1-1/4	.532 - .660	.652 - .780
PT-4	Eight-Button	3-1/8	2-3/4	13-1/8	1-3/4	.652 - .780	.760 - .886
PT-5	Ten-Button	3-1/8	2-3/4	16	2	—	.760 - .886
PT-6	Twelve Button	3-1/8	2-3/4	18-1/4	2-1/4	—	.890 - 1.125

† Specify Cable Diameter when the Cable Used is not within the Range Listed.



PT-6L



PC-5R
PC-5L
PT-5L



PC-4R
PC-4L
PT-4R
PT-4L



PC-3R
PC-3L
PT-3R
PT-3L



PC-2



PC-1

Pictures are for illustration purposes and may not represent actual product.